

C360 Corn Cobb



The C360 features the 3rd generation Samsung 5630 LED chip with the latest in Rubycon capacitors and JAE connectors. The design includes 6063 grade aluminum with specialized fins that allows the C360 to be installed in enclosed fixtures.

The C360 is recommended for installation in area lighting fixtures, streetlights, wall packs and for use as high bay retrofits. DLC available on 27W and above only.

Part Number	Wattage	Replaces in HID	Lumens	CCT	Voltage	Beam Angle	Power Factor	Base Options
IL-C360-14W-(CCT)-E26	14W	50W	1680 lm	40K - 4000K, 50K - 5000K	100V - 277V AC	360°	>0.9	MED/E26
IL-C360-22W-(CCT)-E26	22W	100W	2640 lm					MED/E26 OR MOG/E40
IL-C360-27W-(CCT)-E26/E39*	27W	150W	3240 lm					MED/E26 OR MOG/E40
IL-C360-36W-(CCT)-E26/E39*	36W	175W	4320 lm					MED/E26 OR MOG/E40
IL-C360-54W-(CCT)-E26/E39*	54W	250W	6480 lm					MED/E26 OR MOG/E40
IL-C360-80W-(CCT)-E40*	80W	300W	9,600 lm					MED/E26 OR MOG/E40
IL-C360-120W-(CCT)-E40*	120W	450W	14,400 lm					MED/E26 OR MOG/E40

Warranty:
5 Year Warranty
LED Rated Life:
70,000 hours

Working Temperature:
-4° F to 122° F
Protection Grade:
IP64

Available Colors (CCT):
30K-3000K, 40K-4000K, 50K-5000K
*Replace (CCT) in the part number with Color Temperature abbreviation above.

Iconic LED, LLC
1806 W Pinhook Rd.
Lafayette, LA 70508
Main (337) 456-3477
sales@iconicled.com

