



# The iFlood

80W, 100W, 150W, 220W, 300W

The Iconic LED iFlood is a versatile flood light that can be used for area lighting, parking lots, and other flood applications. The lights are easily integrated with external controls. These lights are suitable for wet locations.

Model Number	Wattage	Replaces in HID	CCT (K)	Lumens	Efficacy (lm/W)	Input Voltage	CRI	Power Factor
IFL-80W-50K	79W	250W	5000K	9,064 lm	115 lm/W	100V - 277V	85	>0.95
IFL-100W-50K	98W	300W	5000K	11,021 lm	112 lm/W		84	
IFL-150W-50K	154W	400W	5000K	15,131 lm	98 lm/W		83	
IFL-220W-50K	220W	550W	5000K	25,684 lm	116 lm/W		85	
IFL-300W-50K	304W	800W	5000K	30,857 lm	101 lm/W		84	

**Warranty:**  
5 Year Warranty  
**LED Rated Life:**  
50,000 hours

**Working Temperature:**  
-22° F to 140° F  
**Protection Grade:**  
IP65

**Available Colors (CCT):**  
**50K-5000K**  
\*Comes standard with yoke mount.  
Slip fitter or Arm Mount Sold Separately.

Iconic LED, LLC  
1806 W Pinhook Rd.  
Lafayette, LA 70508  
Main (337) 456-3477  
sales@iconicled.com

iconic led